

## SAFETY DATA SHEET

Version 6.12  
Revision Date 03/02/2024  
Print Date 04/28/2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Lithium tri-*tert*-butoxyaluminum hydride solution

Product Number : 241814  
Brand : Aldrich

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765  
Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225  
Chemicals which, in contact with water, emit flammable gases (Category 1), H260  
Acute toxicity, Oral (Category 4), H302  
Skin corrosion (Category 1B), H314

Aldrich - 241814

Page 1 of 14

Serious eye damage (Category 1), H318

Carcinogenicity (Category 2), H351

Specific target organ toxicity - single exposure (Category 3), Respiratory system, Central nervous system, H335, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H260

In contact with water releases flammable gases which may ignite spontaneously.

H302

Harmful if swallowed.

H314

Causes severe skin burns and eye damage.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

H351

Suspected of causing cancer.

Precautionary Statements

P201

Obtain special instructions before use.

P202

Do not handle until all safety precautions have been read and understood.

P210

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P223

Do not allow contact with water.

P231 + P232

Handle under inert gas. Protect from moisture.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P261

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264

Wash skin thoroughly after handling.

P270

Do not eat, drink or smoke when using this product.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P312 + P330

IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P402 + P404	Store in a dry place. Store in a closed container.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Reacts violently with water., In use may form flammable/explosive vapor-air mixture., May form explosive peroxides.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Formula :  $C_{12}H_{28}AlLiO_3$   
Molecular weight : 254.27 g/mol

Component		Classification	Concentration
<b>Tetrahydrofuran</b>			
CAS-No.	109-99-9	Flam. Liq. 2; Acute Tox. 4; Eye Irrit. 2A; Carc. 2; STOT SE 3; H225, H302, H319, H351, H335, H336 Concentration limits: >= 25 %: Eye Irrit. 2, H319; >= 25 %: STOT SE 3, H335;	>= 90 - <= 100 %
EC-No.	5-53		
Index-No.	603-025-00-0		
Registration number	01-2119444314-46-XXXX		
<b>lithium aluminum tri-tert.-butoxide hydride</b>			
CAS-No.	17476-04-9	1; Skin Corr. 1B; Eye Dam. 1; H260, H314, H318	>= 30 - < 50 %
EC-No.	241-490-8		

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

**If inhaled**

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

**In case of skin contact**

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

**In case of eye contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

**If swallowed**

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Dry powder Dry sand

**Unsuitable extinguishing media**

Do NOT use water jet.

**5.2 Special hazards arising from the substance or mixture**

Carbon oxides

Lithium oxides

Aluminum oxide

Combustible.

**5.3 Advice for firefighters**

Wear self-contained breathing apparatus for firefighting if necessary.

**5.4 Further information**

No data available

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

## **6.2 Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## **6.3 Methods and materials for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush with water.

## **6.4 Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

#### **Advice on safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

#### **Advice on protection against fire and explosion**

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

#### **Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

For precautions see section 2.2.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Never allow product to get in contact with water during storage.

Store under inert gas. Dry residue is explosive. Test for peroxide formation periodically and before distillation. Dry residue is explosive. Store under inert gas. Test for peroxide formation periodically and before distillation.

#### **Storage class**

Storage class (TRGS 510): 4.3: Hazardous materials, which set free flammable gases upon contact with water

### **7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Ingredients with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
Tetrahydrofuran	109-99-9	TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption		
		STEL	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption		
		ST	250 ppm 735 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	200 ppm 590 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	200 ppm 590 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	200 ppm 590 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	250 ppm 735 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Tetrahydrofuran	109-99-9	Tetrahydrofuran	2 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

## 8.2 Exposure controls

### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### Personal protective equipment

#### Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact

with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 10 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

---

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

- |  |                            |
|--|----------------------------|
| a) Appearance                              | Form: liquid               |
| b) Odor                                    | No data available          |
| c) Odor Threshold                          | No data available          |
| d) pH                                      | No data available          |
| e) Melting point/freezing point            | No data available          |
| f) Initial boiling point and boiling range | No data available          |
| g) Flash point                             | -17 °C (1 °F) - closed cup |
| h) Evaporation rate                        | No data available          |
| i) Flammability (solid, gas)               | No data available          |

Aldrich - 241814

Page 7 of 14

j)	Upper/lower flammability or explosive limits	No data available
k)	Vapor pressure	No data available
l)	Vapor density	No data available
m)	Density	0.904 g/cm <sup>3</sup>
	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n-octanol/water	No data available
p)	Autoignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	Not classified as explosive.
t)	Oxidizing properties	none

## 9.2 Other safety information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.  
Reacts violently with water.

### 10.4 Conditions to avoid

Heat, flames and sparks. Exposure to moisture.

### 10.5 Incompatible materials

Strong oxidizing agents, Oxygen, Alcohols, Reacts violently with water.

### 10.6 Hazardous decomposition products

In the event of fire: see section 5



---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Mixture

##### Acute toxicity

Oral: No data available

Acute toxicity estimate Oral - 1,650 mg/kg

(Calculation method)

Inhalation: No data available

Dermal: No data available

Acute toxicity estimate Dermal - 2,500 mg/kg

(Calculation method)

##### Skin corrosion/irritation

No data available

##### Serious eye damage/eye irritation

No data available

##### Respiratory or skin sensitization

No data available

##### Germ cell mutagenicity

No data available

##### Carcinogenicity

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Tetrahydrofuran)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

##### Reproductive toxicity

No data available

##### Specific target organ toxicity - single exposure

No data available

##### Specific target organ toxicity - repeated exposure

No data available

##### Aspiration hazard

No data available

### 11.2 Additional Information

Central nervous system depression, Cough, chest pain, Difficulty in breathing, Exposure to high airborne concentrations can cause anesthetic effects., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Stomach - Irregularities - Based on Human Evidence

## Components

### Tetrahydrofuran

#### Acute toxicity

LD50 Oral - Rat - male and female - 1,650 mg/kg

Remarks: (ECHA)

Symptoms: Irritation of mucous membranes

LC50 Inhalation - Rat - male and female - 6 h - > 14.7 mg/l - vapor  
(US-EPA)

LD50 Dermal - Rat - male and female - > 2,000 mg/kg  
(OECD Test Guideline 402)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 72 h

(Draize Test)

Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis,  
due to degreasing properties of the product.

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

Remarks: (IUCLID)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table  
3.1/3.2)

#### Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

#### Germ cell mutagenicity

Test Type: Ames test

Test system: *S. typhimurium*

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Red blood cells (erythrocytes)

Result: negative

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

No data available

#### Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table  
3.1/3.2)

May cause drowsiness or dizziness.  
Acute oral toxicity - Irritation of mucous membranes

**Specific target organ toxicity - repeated exposure**

**Aspiration hazard**

No data available

**lithium aluminum tri-tert.-butoxide hydride**

**Acute toxicity**

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Symptoms: Shortness of breath, Cough, mucosal irritations

Dermal: No data available

**Skin corrosion/irritation**

Remarks: Causes skin burns.

**Serious eye damage/eye irritation**

Remarks: Causes serious eye damage.

**Respiratory or skin sensitization**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**Specific target organ toxicity - single exposure**

Acute oral toxicity - If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Acute inhalation toxicity - Shortness of breath, Cough, mucosal irritations

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Mixture**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

Aldrich - 241814

Page 11 of 14

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

No data available

##### Components

##### Tetrahydrofuran

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 2,160 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 3,485 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to fish(Chronic toxicity)	flow-through test NOEC - Pimephales promelas (fathead minnow) - 216 mg/l - 33 d Remarks: (ECHA)

##### lithium aluminum tri-tert.-butoxide hydride

No data available

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Contact a licensed professional waste disposal service to dispose of this material.

##### Contaminated packaging

Dispose of as unused product.

---

### SECTION 14: Transport information

#### DOT (US)

Aldrich - 241814

Page 12 of 14

UN number: 3399 Class: 4.3 (3) Packing group: I  
Proper shipping name: Organometallic substance, liquid, water-reactive, flammable  
(Tetrahydrofuran, lithium aluminum tri-tert.-butoxide hydride)  
Reportable Quantity (RQ): 1000 lbs  
Poison Inhalation Hazard: No

#### IMDG

UN number: 3399 Class: 4.3 (3) Packing group: I EMS-No: F-G, S-N  
Proper shipping name: ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE,  
FLAMMABLE (lithium aluminum tri-tert.-butoxide hydride, Tetrahydrofuran)

#### IATA

UN number: 3399 Class: 4.3 (3) Packing group: I  
Proper shipping name: Organometallic substance, liquid, water-reactive, flammable (lithium  
aluminum tri-tert.-butoxide hydride, Tetrahydrofuran)  
IATA Passenger: Not permitted for transport

---

## SECTION 15: Regulatory information

### SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### SARA 311/312 Hazards

Fire Hazard, Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

### Massachusetts Right To Know Components

	CAS-No.	Revision Date
Tetrahydrofuran	109-99-9	1993-02-16

	CAS-No.	Revision Date
Tetrahydrofuran	109-99-9	1993-02-16

### Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Tetrahydrofuran	109-99-9	1993-02-16

lithium aluminum tri-tert.-butoxide hydride	17476-04-9
---	------------

	CAS-No.	Revision Date
Tetrahydrofuran	109-99-9	1993-02-16

### New Jersey Right To Know Components

	CAS-No.	Revision Date
--	---------	---------------

Aldrich - 241814

Page 13 of 14

	109-99-9	1993-02-16
lithium aluminum tri-tert.-butoxide hydride	17476-04-9	
<b>California Prop. 65 Components</b>		
, which is/are known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .Tetrahydrofuran	CAS-No. 109-99-9	Revision Date 2021-12-31

---

## SECTION 16: Other information

### Further information

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 6.12

Revision Date: 03/02/2024

Print Date: 04/28/2024