

• SAFETY DATA SHEET

Version 7.4
Revision Date 01/27/2026
Print Date 01/28/2026

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Lithium tri-*tert*-butoxyaluminum hydride solution

Product Number : 241814
Brand : Aldrich

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 2

Chemicals which, in contact with water, emit flammable gases	: Category 1
Skin corrosion	: Sub-category 1B
Serious eye damage	: Category 1
Carcinogenicity	: Category 2
Specific target organ toxicity - single exposure	: Category 3 (Central nervous system)

Other hazards

Reacts violently with water.
May form explosive peroxides.

GHS label elements

Hazard pictograms	:	   
-------------------	---	--

Signal word	: Danger
-------------	----------

Hazard statements	: H225 Highly flammable liquid and vapour. H260 In contact with water releases flammable gases which may ignite spontaneously. H314 Causes severe skin burns and eye damage. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.
-------------------	--

Supplemental Hazard Statements	: Corrosive to the respiratory tract.
--------------------------------	---------------------------------------

Precautionary statements	: Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P223 Do not allow contact with water. P231 + P232 Handle and store contents under inert gas. Protect from moisture. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges.
--------------------------	--

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302 + P335 + P334 IF ON SKIN: Brush off loose particles from skin. Immerse in cool water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P402 + P404 Store in a dry place. Store in a closed container.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

CAS-No. : Not Assigned

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Tetrahydrofuran	109-99-9*	>= 65 - <= 85	TSC

lithium aluminum tri-tert.-butoxide hydride	17476-04-9*	$\geq 10 - \leq 30$	TSC
---	-------------	---------------------	-----

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: First aiders need to protect themselves. Show this safety data sheet to the doctor in attendance.
If inhaled	: After inhalation: fresh air. Call in physician.
In case of skin contact	: In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.
In case of eye contact	: After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.
If swallowed	: After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.
Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO ₂) Dry powder
Unsuitable extinguishing media	: Water Foam
Specific hazards during fire fighting	: Combustible.

Pay attention to flashback.

Vapours are heavier than air and may spread along floors.

May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Hazardous combustion products : Carbon oxides

Lithium oxides

Aluminum oxide

Specific extinguishing methods : No data available

Further information : Remove container from danger zone and cool with water.
Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for fire-fighters : Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Advice for non-emergency personnel:
Do not breathe vapours, aerosols.
Avoid substance contact.
Ensure adequate ventilation.
Keep away from heat and sources of ignition.
Evacuate the danger area, observe emergency procedures, consult an expert.
Advice for emergency responders:
For personal protection see section 8.

Environmental precautions	: Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

Advice on protection against fire and explosion	: Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
Advice on safe handling	: Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep workplace dry. Do not allow product to come into contact with water.
Further information on storage conditions	: Tightly closed. Keep away from heat and sources of ignition.
Materials to avoid	: Never allow product to get in contact with water during storage.
Storage class	: 4.3, Hazardous materials, which set free flammable gases upon contact with water
Recommended storage temperature	: / 36 - 46 °F / 2 - 8 °C /
Further information on storage stability	: Store under inert gas. Dry residue is explosive. Test for peroxide formation periodically and before distillation. Test for peroxide formation periodically and before distillation.
Packaging material	: Suitable material: Sure-Seal Bottles

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Tetrahydrofuran	109-99-9	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		ST	250 ppm 735 mg/m ³	NIOSH REL
		TWA	200 ppm 590 mg/m ³	NIOSH REL
		TWA	200 ppm 590 mg/m ³	OSHA Z-1
lithium aluminum tri-tert.-butoxide hydride	17476-04-9	TWA (Respirable particulate matter)	1 mg/m ³ (Aluminium)	ACGIH
		TWA	2 mg/m ³ (Aluminium)	NIOSH REL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Tetrahydrofuran	109-99-9	Tetrahydrofuran	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material	: butyl-rubber
Break through time	: 10 min
Glove thickness	: 0.3 mm
Protective index	: Splash contact
Manufacturer	: Butoject® (KCL 897 / Aldrich Z677647, Size M)
Manufacturer	: data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374
Remarks	: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.
Eye protection	: Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles
Skin and body protection	: Flame retardant antistatic protective clothing.
Hygiene measures	: Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: No data available

Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Melting point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 1 °F / -17 °C
	Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.904 g/cm ³
Water solubility	: No data available
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Molecular weight	: 254.27 g/mol
Particle characteristics	
Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Formation of peroxides possible. Vapours may form explosive mixture with air.
Chemical stability	: sensitive to moisture
Possibility of hazardous reactions	: No data available
Conditions to avoid	: Warming. Moisture.
Incompatible materials	: Strong oxidizing agents Oxygen Alcohols Reacts violently with water.
Hazardous decomposition products	: Peroxides : In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Acute toxicity estimate Oral - 2,200 mg/kg

(Calculation method)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Dermal: No data available

Acute toxicity estimate Dermal - 3,333 mg/kg
(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes burns.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye damage.
Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Evidence of a carcinogenic effect.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Tetrahydrofuran)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture may cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Central nervous system depression, Cough, chest pain, Difficulty in breathing, Exposure to high airborne concentrations can cause anesthetic effects., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence

Components

Tetrahydrofuran

Acute toxicity

LD50 Oral - Rat - male and female - 1,650 mg/kg

Remarks: (ECHA)

Aldrich - 241814

Page 11 of 19

Symptoms: Irritation of mucous membranes
LC50 Inhalation - Rat - male and female - 6 h - > 14.7 mg/l - vapour
(US-EPA)
LD50 Dermal - Rat - male and female - > 2,000 mg/kg
(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 72 h

(Draize Test)

Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Serious eye damage/eye irritation

Eyes - Rabbit

(Evaluated according F.H.S.A.= Federal Hazardous Substance Act.)

Remarks: Causes serious eye damage.

(ECHA)

Eyes - Rabbit

(Tested according to Annex V of Directive 67/548/EEC.)

Remarks: Causes serious eye damage.

(ECHA)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: *S. typhimurium*

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Red blood cells (erythrocytes)

Result: negative

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

May cause drowsiness or dizziness.

Acute oral toxicity - Irritation of mucous membranes

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

lithium aluminum tri-tert.-butoxide hydride

Acute toxicity

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Symptoms: Shortness of breath, Cough, mucosal irritations

Dermal: No data available

Skin corrosion/irritation

Remarks: Causes skin burns.

Serious eye damage/eye irritation

Remarks: Causes serious eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Acute oral toxicity - If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Acute inhalation toxicity - Shortness of breath, Cough, mucosal irritations

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Tetrahydrofuran:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,160 mg/l
End point: mortality
Exposure time: 96 h
Test Type: flow-through test
Analytical monitoring: yes

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,485 mg/l
End point: mortality
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 216 mg/l
End point: Growth inhibition
Exposure time: 33 d
Test Type: flow-through test
Analytical monitoring: yes
Remarks: (ECHA)

Persistence and degradability

Components:

Tetrahydrofuran:

Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 2 mg/l
Biochemical oxygen demand
Result: Not readily biodegradable.
Biodegradation: 39 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

Tetrahydrofuran:

Partition coefficient: n-octanol/water : log Pow: 0.45 (77 °F / 25 °C)
Method: OECD Test Guideline 107
Remarks: Bioaccumulation is not expected.

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

Tetrahydrofuran:

Results of PBT and vPvB assessment : Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

lithium aluminum tri-tert.-butoxide hydride:

Additional ecological information : Discharge into the environment must be avoided.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3399
Proper shipping name : Organometallic substance, liquid, water-reactive, flammable (lithium aluminum tri-tert.-butoxide hydride, Tetrahydrofuran)
Class : 4.3
Subsidiary risk : 3
Packing group : I
Labels : Division 4.3 - Substances which in contact with water emit flammable gases, Class 3 - Flammable liquids
Packing instruction (cargo aircraft) : 494
Packing instruction (passenger aircraft) : Not permitted for transport

IMDG-Code

UN number : UN 3399
Proper shipping name : ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE (lithium aluminum tri-tert.-butoxide hydride, Tetrahydrofuran)
Class : 4.3
Subsidiary risk : 3
Packing group : I

Aldrich - 241814

Page 15 of 19

Labels : 4.3 (3)
EmS Code : F-G, S-N
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR Road

UN/ID/NA number : UN 3399
Proper shipping name : Organometallic substance, liquid, water-reactive, flammable
(Tetrahydrofuran, lithium aluminum tri-tert.-butoxide hydride)
Class : 4.3
Subsidiary risk : 3
Packing group : I
Labels : Division 4.3 - Substances which in contact with water emit flammable gases, Class 3 - Flammable liquids
ERG Code : 138
Marine pollutant : no

Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Tetrahydrofuran	109-99-9	1000	1333

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Reactivity Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations**Massachusetts Right To Know**

Tetrahydrofuran	109-99-9
-----------------	----------

Pennsylvania Right To Know

Tetrahydrofuran	109-99-9
lithium aluminum tri-tert.-butoxide hydride	17476-04-9

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including Tetrahydrofuran, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United

Aldrich - 241814

Page 18 of 19

States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 01/27/2026

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

US / EN