

• SAFETY DATA SHEET

Version 9.0
Revision Date 10/16/2025
Print Date 10/17/2025

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Toluene

Product Number : PHR1311
Brand : Sigma-Aldrich
Index-No. : 601-021-00-3
CAS-No. : 108-88-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 2

Skin irritation	: Category 2
Reproductive toxicity	: Category 2
Specific target organ toxicity - single exposure	: Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhalation)	: Category 2 (Central nervous system)
Aspiration hazard	: Category 1
Short-term (acute) aquatic hazard	: Category 2
Long-term (chronic) aquatic hazard	: Category 3

Other hazards

None known.

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

CAS-No. : 108-88-3

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Toluene	108-88-3*	>= 80 - <= 100	TSC

* Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice	: Show this safety data sheet to the doctor in attendance.
If inhaled	: After inhalation: fresh air. Call in physician.
In case of skin contact	: In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
In case of eye contact	: After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.
If swallowed	: After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.
Most important symptoms and effects, both acute and delayed	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Protection of first-aiders	: For personal protection see section 8.
Notes to physician	: No data available

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO ₂) Dry powder
Unsuitable extinguishing media	: For this substance/mixture no limitations of extinguishing agents are given.
Specific hazards during fire fighting	: Combustible.

Pay attention to flashback.

Vapours are heavier than air and may spread along

floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Specific extinguishing methods	: No data available
Further information	: Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.
Environmental precautions	: Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take precautionary measures against static discharge.
- Advice on safe handling : Work under hood. Do not inhale substance/mixture.
Avoid generation of vapours/aerosols.
- Further information on storage conditions : Keep container tightly closed in a dry and well-ventilated place.
Keep away from heat and sources of ignition.
- Storage class : 3, Flammable liquids
- Recommended storage temperature : -70°C Degree Freezer
- Further information on storage stability : Store at Room Temperature.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	100 ppm 375 mg/m ³	OSHA P0
		STEL	150 ppm 560 mg/m ³	OSHA P0
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI

				ek		
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.
Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material : Viton®
Break through time : 480 min
Glove thickness : 0.7 mm
Protective index : Full contact
Manufacturer : Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Material : Viton®
Break through time : 480 min
Glove thickness : 0.7 mm
Protective index : Splash contact

Manufacturer	: Vitoject® (KCL 890 / Aldrich Z677698, Size M)
Remarks	: This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).
Eye protection	: Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses
Skin and body protection	: Flame retardant antistatic protective clothing.
Hygiene measures	: Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid (68 °F / 20 °C, 1,013 hPa)
Color	: No data available
Odor	: benzene-like
Odor Threshold	: 0.2 ppm
pH	: Not applicable
Melting point/ range	: -139 - -135 °F / -95 - -93 °C
Boiling point/boiling range	: 231.1 °F / 110.6 °C (1,013 hPa)
Flash point	: 39.9 °F / 4.4 °C (1,013 hPa) Method: closed cup, closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available

Burning rate	: No data available
Upper explosion limit / Upper flammability limit	: Upper explosion limit 7.1 %(V)
Lower explosion limit / Lower flammability limit	: Lower explosion limit 1.2 %(V)
Vapor pressure	: 30.88 hPa (70.0 °F / 21.1 °C)
Relative vapour density	: 3.18
Relative density	: No data available
Density	: 0.87 g/cm ³ (68 °F / 20 °C)
Solubility(ies) Water solubility	: 0.58 g/l partly soluble (77 °F / 25 °C) pH: 7
Partition coefficient: n- octanol/water	: log Pow: 2.73 (68 °F / 20 °C) pH: 7 Bioaccumulation is not expected.
Autoignition temperature	: 896 °F / 480 °C (1,013.25 hPa)
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: 0.56 mPa.s (77 °F / 25 °C)
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Surface tension	: 27.73 mN/m, 0.516 g/l, 77 °F / 25 °C
Conductivity	: < 0.01 µS/cm
Molecular weight	: 92.14 g/mol
Particle characteristics Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapours may form explosive mixture with air. Vapours may form explosive mixture with air.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) . The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: Risk of explosion with: fuming sulfuric acid Nitric acid silver perchlorates nitrogen dioxide nonmetallic halides halogen-halogen compounds uranium hexafluoride organic nitro compounds Violent reactions possible with: Strong acids Strong oxidizing agents sulfur with Heat
Conditions to avoid	: Warming. Warming.
Incompatible materials	: No data available
Hazardous decomposition products	: In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 5,580 mg/kg

(Directive 67/548/EEC, Annex V, B.1.)

LC50 Inhalation - Rat - male - 4 h - 25.7 mg/l - vapour

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male - > 5,000 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: irritating - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximisation Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Ames test

Test system: *S. typhimurium*

Metabolic activation: with and without metabolic activation

Method: Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)

Result: negative

Test Type: Chromosome aberration test

Species: Rat

Cell type: Bone marrow

Application Route: Intraperitoneal

Result: negative

Remarks: (ECHA)

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary oedema and pneumonitis.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - No observed adverse effect level - 625 mg/kg - Lowest observed adverse effect level - 1,250 mg/kg

Stomach - Irregularities - Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Toluene:**

Toxicity to fish	: LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l End point: mortality Exposure time: 96 h Test Type: flow-through test Analytical monitoring: yes Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l End point: mortality Exposure time: 48 h Analytical monitoring: yes Method: US-EPA
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l End point: Growth inhibition Exposure time: 40 d Test Type: flow-through test Analytical monitoring: yes Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l End point: reproduction rate Exposure time: 7 d Analytical monitoring: yes Method: US-EPA
Toxicity to microorganisms	: EC50 (Bacteria): 84 mg/l Exposure time: 24 h Test Type: static test Remarks: (ECHA)

Persistence and degradability

Components:

Toluene:

Biodegradability : aerobic
Result: Readily biodegradable.
Biodegradation: 86 %
Exposure time: 20 d
Remarks: (IUCLID)

Bioaccumulative potential

Components:

Toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90
Exposure time: 3 d
Concentration: 0.05 mg/l

Partition coefficient: n-octanol/water : log Pow: 2.73 (68 °F / 20 °C)
pH: 7
Remarks: Bioaccumulation is not expected.

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

Sigma-Aldrich - PHR1311

Page 13 of 17

IATA-DGR

UN/ID No. : UN 1294
Proper shipping name : Toluene
Class : 3
Packing group : II
Labels : Class 3 - Flammable liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1294
Proper shipping name : TOLUENE

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations**49 CFR Road**

UN/ID/NA number : UN 1294
Proper shipping name : Toluene

Class : 3
Packing group : II
Labels : Class 3 - Flammable liquids
ERG Code : 130
Marine pollutant : no

Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	1000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

This product contains the following priority pollutants related to the U.S. Clean Water Act:

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

US State Regulations

Massachusetts Right To Know

Toluene	108-88-3
---------	----------

Pennsylvania Right To Know

Toluene	108-88-3
---------	----------

Maine Chemicals of High Concern

Toluene	108-88-3
---------	----------

Vermont Chemicals of High Concern

Toluene	108-88-3
---------	----------

Washington Chemicals of High Concern

Toluene

108-88-3

California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Relevant changes since previous version

16. Other information

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous

Sigma-Aldrich - PHR1311

Page 16 of 17

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2025 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 10/16/2025

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

US / EN