

SAFETY DATA SHEET

Version 6.8 Revision Date 03/02/2024 Print Date 03/23/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Methanol

Product Number : 320390 Brand : SIGALD

Index-No. : 603-001-00-X CAS-No. : 67-56-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331

SIGALD - 320390

Page 1 of 13



Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system, H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs (Eyes, Central nervous system).

Precautionary Statements

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.

P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Methyl alcohol

SIGALD - 320390

Page 2 of 13



Formula : CH_4O

Molecular weight : 32.04 g/mol CAS-No. : 67-56-1 EC-No. : 200-659-6 Index-No. : 603-001-00-X

| Component | Classification | Concentration |
|-----------|---|---------------|
| Methanol | | |
| | Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 | <= 100 % |
| | Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371; | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

No data available

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

No data available

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible.

5.3 Advice for firefighters

No data available

5.4 Further information

No data available



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8.

6.2 Environmental precautions

No data available

6.3 Methods and materials for containment and cleaning up

No data available

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

No data available

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

| Component | CAS-No. | Value | Control | Basis |
|-----------|---------|---------------------------------|------------|---|
| | | | parameters | |
| Methanol | 67-56-1 | TWA | 200 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | | _ | <u> </u> | ` , |
| | Remarks | Danger of cutaneous absorption | | |
| | | STEL | 250 ppm | USA. ACGIH Threshold Limit |
| | | | | Values (TLV) |
| | | Danger of cutaneous absorption | | |
| | | ST | 250 ppm | USA. NIOSH Recommended |
| | | | 325 mg/m3 | Exposure Limits |
| | | Potential for dermal absorption | | |
| | | TWA | 200 ppm | USA. NIOSH Recommended |
| | | | 260 mg/m3 | Exposure Limits |
| | | Potential for dermal absorption | | |



| TWA | 200 ppm 260 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
|------|----------------------|---|
| PEL | 200 ppm 260 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| Skin | | |
| С | 1,000 ppm | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| Skin | | |
| STEL | 250 ppm 325 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| Skin | | |

Biological occupational exposure limits

| biological occupational exposure mints | | | | | |
|--|---------|----------------|-------------|---------------------|--|
| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
| Methanol | 67-56-1 | Methanol | 15 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | End of shift (| (As soon as | possible after ex | oosure ceases) |

Derived No Effect Level (DNEL)

| Delived No Ellec | t Level (DIVLE | | |
|------------------|----------------|----------------------------|--------------|
| Application Area | Routes of | Health effect | Value |
| | exposure | | |
| Workers | Skin contact | Long-term systemic effects | 40mg/kg BW/d |
| Consumers | Skin contact | Long-term systemic effects | 8mg/kg BW/d |
| Consumers | Ingestion | Long-term systemic effects | 8mg/kg BW/d |
| Workers | Skin contact | Acute systemic effects | 40mg/kg BW/d |
| Consumers | Skin contact | Acute systemic effects | 8mg/kg BW/d |
| Consumers | Ingestion | Acute systemic effects | 8mg/kg BW/d |
| Workers | Inhalation | Acute systemic effects | 260 mg/m3 |
| Workers | Inhalation | Acute local effects | 260 mg/m3 |
| Workers | Inhalation | Long-term systemic effects | 260 mg/m3 |
| Workers | Inhalation | Long-term local effects | 260 mg/m3 |
| Consumers | Inhalation | Acute systemic effects | 50 mg/m3 |
| Consumers | Inhalation | Acute local effects | 50 mg/m3 |
| Consumers | Inhalation | Long-term systemic effects | 50 mg/m3 |
| Consumers | Inhalation | Long-term local effects | 50 mg/m3 |

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|-------------|------------|
| Soil | 23.5 mg/kg |
| Sea water | 15.4 mg/l |

SIGALD - 320390 Page 5 of 13



| Fresh water | 154 mg/l |
|-------------------------------|-------------|
| Fresh water sediment | 570.4 mg/kg |
| Onsite sewage treatment plant | 100 mg/kg |

8.2 Exposure controls

Personal protective equipment

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

internet: www.kci.de)

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 120 min

Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Control of environmental exposure

Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor characteristic

c) Odor Threshold 10 ppm

d) pH No data available

e) Melting point/range: -98 °C (-144 °F)

point/freezing point

f) Initial boiling point 64.7 °C 148.5 °F

and boiling range

g) Flash point 9.7 °C (49.5 °F) - closed cup - Regulation (EC) No. 440/2008,

Annex, A.9

h) Evaporation rate 6.3 - Diethyl ether 1.9 - n-butyl acetate

SIGALD - 320390

Page 6 of 13



i) Flammability (solid,

No data available

gas)

Upper/lower j) flammability or explosive limits Upper explosion limit: 44 %(V) Lower explosion limit: 5.5 %(V)

k) Vapor pressure

169.27 hPa at 25 °C (77 °F)

Vapor density I)

1.11

m) Density

0.791 g/mL at 25 °C (77 °F)

Relative density

0.79 - 0.820 °C

n) Water solubility

1,000 g/l at 20 °C (68 °F) - completely miscible

o) Partition coefficient: n-octanol/water

log Pow: -0.77 at 25 °C (77 °F) - (HSDB), Bioaccumulation is

not expected.

p) Autoignition temperature

Viscosity

r)

455.0 °C (851.0 °F) at 1,013 hPa - DIN 51794

q) Decomposition

Distillable in an undecomposed state at normal pressure.

temperature

0.54 - 0.59 mm2/s at 20 °C (68 °F) -

s) Explosive properties

No data available

t) Oxidizing properties none

Other safety information 9.2

Minimum ignition

energy

0.14 mJ

Conductivity

 $< 1 \mu S/cm$

Relative vapor

density

1.11

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

Risk of explosion with: Oxidizing agents perchloric acid perchlorates salts of oxyhalogenic acids chromium(VI) oxide halogen oxides

nitrogen oxides

SIGALD - 320390

illiPOR*e*

nonmetallic oxides

chromosulfuric acid

chlorates

hydrides

zinc diethyl

halogens

powdered magnesium

hydrogen peroxide

Nitric acid

sulfuric acid

permanganic acid

sodium hypochlorite

Exothermic reaction with:

acid halides

Acid anhydrides

Reducing agents

acids

Bromine

Chlorine

Chloroform

magnesium

tetrachloromethane

Risk of ignition or formation of inflammable gases or vapours with:

Fluorine

Oxides of phosphorus

Raney-nickel

Generates dangerous gases or fumes in contact with:

Alkaline earth metals

Alkali metals

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

SIGALD - 320390

Page 8 of 13

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation Remarks: (ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: PC1400000

Acute effects:, Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma

Drying-out effect resulting in rough and chapped skin.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

acidosis
drop in blood pressure
agitation, spasms
inebriation
Dizziness
Drowsiness
Headache
Impairment of vision
Blindness
narcosis
Coma

Symptoms may be delayed.

Damage to:

Liver Kidney

Cardiac

Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SIGALD - 320390

AilliPDRE

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15,400.0

mg/l - 96 h (US-EPA)

Toxicity to daphnia

semi-static test EC50 - Daphnia magna (Water flea) - 18,260 mg/l -

and other aquatic invertebrates

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca.

22,000.0 mg/l - 96 h (OECD Test Guideline 201)

Toxicity to bacteria $\,$ static test IC50 - activated sludge - > 1,000 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to NOEC - Oryzias latipes (Orange-red killifish) - 7,900 mg/l - 200 h

fish(Chronic toxicity) Remarks: (External MSDS)

12.2 Persistence and degradability

Biodegradability Result: 99 % - Readily biodegradable.

(OECD Test Guideline 301D)

Biochemical Oxygen Demand (BOD)

600 - 1,120 mg/g Remarks: (IUCLID)

Chemical Oxygen

1,420 mg/g

Demand (COD)

Remarks: (IUCLID)

Theoretical oxygen demand

1,500 mg/g Remarks: (Lit.)

Ratio BOD/ThBOD

76.0/

Remarks: Closed Bottle test(IUCLID)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 72 d

at 20 °C - 5 mg/l(Methanol)

Bioconcentration factor (BCF): 1.0

12.4 Mobility in soil

Will not adsorb on soil.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Additional ecological Avoid release to the environment.

information

SIGALD - 320390

lilliPOR**e**

Page 11 of 13

Stability in water at 19 °C83 - 91 % - 72 h

Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.

- 2.2 yr

Remarks: reaction with hydroxyl radicals(IUCLID)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: Methanol Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOL

IATA

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: Methanol

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol CAS-No. Revision Date 67-56-1 2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Methanol CAS-No. Revision Date 67-56-1 2007-07-01

SIGALD - 320390

Page 12 of 13

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



Pennsylvania Right To Know Components

Methanol CAS-No. Revision Date 67-56-1 2007-07-01

California Prop. 65 Components

, which is/are known to the State of California to CAS-No. Revision Date cause birth defects or other reproductive harm. For 67-56-1 2012-03-16

more information go to

www.P65Warnings.ca.gov.Methanol

SECTION 16: Other information

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.8 Revision Date: 03/02/2024 Print Date: 03/23/2024

