

SAFETY DATA SHEET

Version 6.7 Revision Date 03/02/2024 Print Date 04/28/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifiers 1.1

Product name Vinyl chloride solution

500976 **Product Number** Brand Supelco

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

> (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

Details of the supplier of the safety data sheet 1.3

Company : Sigma-Aldrich Inc.

> 3050 SPRUCE ST ST. LOUIS MO 63103 **UNITED STATES**

: +1 314 771-5765 Telephone Fax +1 800 325-5052

Emergency telephone

800-424-9300 CHEMTREC (USA) +1-703-Emergency Phone #

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311 Carcinogenicity (Category 1A), H350

Supelco - 500976

Page 1 of 15



Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system, H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

P264

Signal Word Danger Hazard Statements Highly flammable liquid and vapor. H225 Toxic if swallowed, in contact with skin or if inhaled. H301 + H311 + H331 H350 May cause cancer. H370 Causes damage to organs (Eyes, Central nervous system). **Precautionary Statements** P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Keep container tightly closed. P233 P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist or vapors.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Wash skin thoroughly after handling.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician. Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration
Methanol			
CAS-No. EC-No. Index-No. Registration number	67-56-1 200-659-6 603-001-00-X 01-2119433307-44- XXXX	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	>= 90 - <= 100 %
Vinyl chloride			
CAS-No. EC-No. Index-No.	75-01-4 200-831-0 602-023-00-7	Flam. Gas 1; Press. Gas Liquefied gas; Carc. 1A; H220, H280, H350	>= 0.1 - < 1 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour).

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Supelco - 500976

Page 3 of 15



4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

Supelco - 500976



Page 4 of 15

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Danger of cutaneous absorption		
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Danger of cutaneous absorption		
		ST	250 ppm 325 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		
		TWA	200 ppm 260 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		



		TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
		Skin			
		С	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
		Skin	Skin		
		STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
		Skin			
Vinyl chloride	75-01-4	TWA	1 ppm	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)	
		TWA	1 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		Liver damage Lung cancer Confirmed human carcinogen			
		STEL	5 ppm	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)	
		TWA	1 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		STEL	5 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		See 1910.	1017		
		Potential Occupational Carcinogen			
		See Appendix A			

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

Supelco - 500976 Page 6 of 15



8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

Supelco - 500976

AilliPDRe

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

b) Odor No data available

c) Odor Thresholdd) pHNo data availableNo data available

d) pH No data availablee) Melting No data available

f) Initial boiling point No data available and boiling range

point/freezing point

g) Flash point 11.0 °C (51.8 °F) - closed cup - Solvent

h) Evaporation rate No data availablei) Flammability (solid, No data available gas)

j) Upper/lower Upper explosion limit: 36 %(V) flammability or explosive limits Upper explosion limit: 6 %(V)

k) Vapor pressure No data available
l) Vapor density No data available
m) Density No data available
Relative density No data available
n) Water solubility No data available

o) Partition coefficient: No data available n-octanol/water

p) Autoignition No data available temperature

q) Decomposition No data available temperature

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

Supelco - 500976

Millipore SigMa

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

acids, Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Acute toxicity estimate Oral - 100.1 mg/kg

(Calculation method)

Inhalation: No data available

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor(Calculation method)

Dermal: No data available

Acute toxicity estimate Dermal - 300.1 mg/kg

(Calculation method) No data available

Skin corrosion/irritation

Remarks: No data available

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

This is or contains a component that has been reported to be carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

IARC: 1 - Group 1: Carcinogenic to humans (Vinyl chloride)

Supelco - 500976

Page 9 of 15



NTP: Known - Known to be human carcinogen (Vinyl chloride)
OSHA: OSHA specifically regulated carcinogen (Vinyl chloride)

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure

Remarks: No data available

Mixture causes damage to organs. - Eyes, Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Headache, Vomiting, Gastrointestinal disturbance, Dizziness, Weakness, Confusion., Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence

Components

Methanol

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)



Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation Remarks: (ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Acute oral toxicity - Nausea, Vomiting

Acute inhalation toxicity - Irritation symptoms in the respiratory tract.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Vinyl chloride

Acute toxicity

Oral: No data available

LC50 Inhalation - Rat - 2 h - 390 mg/l - gas

Remarks: (ECHA)

Dermal: No data available

Supelco - 500976 Page 11 of 15

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Result: negative Remarks: (ECHA) Test Type: Ames test

Test system: Salmonella typhimurium

Result: positive

Species: Mouse - male and female

Result: negative Remarks: (ECHA)

Method: OECD Test Guideline 474 Species: Mouse - male and female

Result: positive

Carcinogenicity

May cause cancer. Positive evidence from human epidemiological studies.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

 $\label{pbt} PBT/vPvB \ assessment \ not \ available \ as \ chemical \ safety \ assessment \ not \ required/not \ conducted$

Supelco - 500976

Page 12 of 15



12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

Components

Methanol

Toxicity to fish flow-through test LC50 - Lepomis macrochirus (Bluegill) -

15,400.0 mg/l - 96 h

(US-EPA)

Toxicity to daphnia

and other aquatic invertebrates

semi-static test EC50 - Daphnia magna (Water flea) - 18,260

mg/l - 96 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green

algae) - ca. 22,000.0 mg/l - 96 h

(OECD Test Guideline 201)

Toxicity to bacteria static test IC50 - activated sludge - > 1,000 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to NOEC - Oryzias latipes (Orange-red killifish) - 7,900 mg/l - 200

fish(Chronic toxicity) h

Remarks: (External MSDS)

Vinyl chloride

Toxicity to fish semi-static test LC50 - Danio rerio (zebra fish) - 210 mg/l - 96

h

(OECD Test Guideline 203)

Toxicity to bacteria Remarks: (ECHA)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

Supelco - 500976

illipore

Page 13 of 15

SECTION 14: Transport information

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: MethanolSOLUTION

Reportable Quantity (RQ): 500 lbs Reportable Quantity (RQ): 1 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOLSOLUTION

IATA

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: MethanolSOLUTION

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol CAS-No. Revision Date 67-56-1 2007-07-01

75-01-4 2007-07-01

Vinyl chloride

SARA 311/312 Hazards

Fire Hazard, Chronic Health Hazard

Reportable Quantity D043 lbs

Massachusetts Right To Know Components

Methanol CAS-No. Revision Date 67-56-1 2007-07-01

75-01-4 2007-07-01

Vinyl chloride

Pennsylvania Right To Know Components

 Methanol
 CAS-No.
 Revision Date

 67-56-1
 2007-07-01

Supelco - 500976 Page 14 of 15

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



Viriyi Cilionde	75-01-4	2007-07-01
California Prop. 65 Components , which is/are known to the State of California to cause cancer, andVinyl chloride	CAS-No. 75-01-4	Revision Date 2007-09-28
, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.Methanol	CAS-No. 67-56-1	Revision Date 2012-03-16

75-01-4

2007-07-01

SECTION 16: Other information

Vinyl chloride

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.7 Revision Date: 03/02/2024 Print Date: 04/28/2024

