

06929 Timestrip® 12 Months Keychain



General

Each Timestrip® indicator is a small, self-adhesive label that can be attached to or integrated into a product, package or carrying card (see adhesive specification in Appendix 1 below for further details). It monitors elapsed time and indicates when key time markers and a pre-defined elapsed time have been reached. The indication of elapsed time is irreversible. Indicators can be made for many different temperature environments, but each product is calibrated for use in a specific temperature environment.

Timestrip® 12 months keychain is calibrated for use at room temperature. Using this product in other temperature environments may affect its performance.

How to use

Timestrip® indicators are completely inert prior to activation and can be stored at room temperature. To activate remove the small stick on the key chain and push the black lever down into the clear plastic holder. This will press the button on the back of the indicator and release the red dye. When the activation line appears, the indicator is armed and ready to use. The red dye will continue to progress until the maximum elapsed time has been reached.

I) Performance Specifications

Run-Time:	12 months (365 days)
Calibration temperature:	22°C ± 1°C
Accuracy:	± 15 % in time under isothermal conditions
Progress Isotherms:	See Fig. 1
Activation Force*:	49 ± 19.6 N

* Activation is applied by firmly squeezing the blister.

II) Product Specification

Button Position:	Button on Bottom Layer (BOB)
Color of Progressing Front:	Red
Adhesive:	2641 Finger-lift 15/9 mm
Product drawing:	See Fig. 2
Graphics:	See Fig. 3
Usage:	The usage of the product in any assembly or production line must be agreed upon in advance, as it may alter performance specifications.
Other:	Not suitable for immersion in water.

III) Product Construction

The indicator is constructed of a polymeric assembly multilayer and aluminum-plastic laminate. It encapsulates colored oils. All materials are non-toxic.

IV) Storage Conditions (un-activated)

- Store in cool dark environment
- Recommended: 22°C/72°F at 20-80% RH
- Please note that before activation, the product can tolerate short term exposure during transit (hours or a few days) to temperatures in the range -30°C to +55°C. However, long term storage should be under recommended conditions.

VI) Shelf-life

- 3 years from date of shipping



Figure 1: Progress Isotherm





Figure 2: Product Drawing




The vibrant M, Supelco, and Sigma-Aldrich are trademarks of Merck KGaA, Darmstadt, Germany or its affiliates. Detailed information on trademarks is available via publicly accessible resources.
 © 2018 Merck KGaA, Darmstadt, Germany and/or its affiliates. All Rights Reserved.

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada.



Figure 3: Graphics



ii.

Customer approval *			
Name		Title: 12 Month RT LifeInService BOB	
Sign.		Graphic no. 800-121A	
Date		Rev. 3 SH. 1 OF. 1	
	Graphic Designer: Meital D. 28.10.09		
	LIn. Tolerance:±0.5mm.		
	Drawing No.:		
	Printing DWG:		

The vibrant M, Supelco, and Sigma-Aldrich are trademarks of Merck KGaA, Darmstadt, Germany or its affiliates. Detailed information on trademarks is available via publicly accessible resources.
 © 2018 Merck KGaA, Darmstadt, Germany and/or its affiliates. All Rights Reserved.

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada.



Appendix 1

Pressure Sensitive Adhesive Data

Timestrip Adhesive - Product # 2641

	<u>SUBSTANCE</u>		<u>THICKNESS</u>
Adhesive	40gsm		
Tissue	12gsm	Adhesive & Carrier	95 micron
Adhesive	45gsm		
Liner	80gsm	Liner	70 micron

PRODUCT DESCRIPTION

A permanent tape with a tissue carrier. The adhesive is a modified acrylic, offering good UV light and chemical resistance together with high performance especially to difficult surfaces. The liner is a two side release system.

APPLICATIONS

The high tack/adhesion of 2641 makes it especially useful for applications involving the bonding of difficult substrates such as many foams, rubbers and polythene type materials. The product is also useful for various mounting applications.

ADHESIVE PROPERTIES

		<u>20 min</u>	<u>24 hour</u>	<u>TEST METHOD</u>
Adhesion to steel	open side	1300 N/M	1400 N/M	BS7116:1990 - D
	closed side	1300 N/M	1400 N/M	BS7116:1990 - D
Shear Adhesion	open side	5 hours		BS7116:1990 - B
	closed side	5 hours		BS7116:1990 - B
Release of liner from adhesive		10 N/M		BS7116:1990 - E

THERMAL PROPERTIES

Recommended service temperature range	-40°C to 110°C	-40°F to 230°F
Application temperature range	5°C to 60°C	41°F to 140°F

SHELF LIFE

Minimum shelf life when stored in closed cartons away from direct sources of heat and sunlight.

2 Years

HEALTH AND SAFETY INFORMATION

The adhesive conforms to F&DA Regulation 175.105.

Note

Values given are average and should not be taken as a maximum or minimum for specification purposes. Specific technical details, applications information and suggested uses available.

